

PRE-OPERATION CHECK – SCISSOR LIFT



Make: Genie Model: GS2632 Serial Number: G53210A-095903

Operator Name: _____ Signature: _____

Date: _____ Hour Meter: _____

Check item:	Yes	No	N/A
Owner’s manual legible and stored inside the container located on the platform.			
All decals legible and in place.			
Fluid levels checked. (Hydraulic oil, engine oil, coolant, etc.)			
Structural and other critical components and all associated fasteners and pins in place.			
Battery packs in place, properly connected and not leaking.			
Compartment covers in place.			
Electrical components, wiring, and electrical cables			
Hydraulic power unit, reservoir, hoses, fittings, cylinders, and manifolds			
Drive and turntable motors and torque hubs			
Boom wear pads, Gauges, Beacon, Lights			
Tires, wheels, limit switches, warning alarms, horn, fasteners, damage to machine			
(Function Test) Test all controls for proper operation			
Fall Protection Devices (railing, gates, toe boards, anchor/connecting points, etc.)			
Obtained supervisor permission to use the aerial/scissor lift			
Barricade area with 4 cones and danger tape or other appropriate methods.			
Wear appropriate PPE (hard hat, safety glasses, gloves, etc.)			
Ensure you have a valid aerial lift card during lift operation			

WORK AREA INSPECTION CHECKLIST FOR AERIAL / SCISSOR LIFT

Instructions: Before an aerial/scissor lift is used and during use, the operator shall check the area in which the aerial platform lift is to be used for possible hazards such as, but not limited to:

- Drop-offs or holes
- Slopes
- Bumps and floor obstructions
- Debris
- Overhead obstructions and high voltage conductors
- Hazardous locations and atmospheres
- Tools and/or other equipment
- Inadequate surface and support for equipment
- Wind and weather conditions:
 - At 20mph wind speeds or anticipated gusts, lifts will be lowered to maximum height of 20'
 - At 25mph wind speeds or anticipated gusts, lifts will be grounded
- Presence of unauthorized people
- Other possible unsafe conditions

Additional Operators

COMMENTS:

NOTE: This form must be kept on file for 1 year and is subject to review by the Environmental Health and Safety Office. Documentation of repairs shall be maintained with the tractor’s preventive maintenance records.